

V_{RRM} = 400 V
 I_{FAVM} = 9244 A
 I_{FRMS} = 14520 A
 I_{FSM} = 60000 A
 V_{F0} = 0.780 V
 r_F = 0.031 mW

Housingless Welding Diode

5SDD 92Z0400

PRELIMINARY

Doc. No. 5SYA1178-00 March 07

- High forward current capability
- Low forward and reverse recovery losses
- High current application up to 2000 Hz
- For parallel connection, please contact factory

Blocking

V_{RRM}	Repetitive peak reverse voltage	400 V	Half sine waveform, $f = 50$ Hz $T_j = -40...180$ °C
I_{RRM}	Repetitive peak reverse current	50 mA	$V_R = V_{RRM}$

Mechanical

F_M	Mounting force	22 ..50 kN
m	Weight	0.10 kg
D_s	Surface creepage distance	2 mm
D_a	Air strike distance	2 mm




Fig. 1

Outline drawing.

All dimensions are in millimeters and represent nominal values unless stated otherwise.

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.

ABB

On-state

I_{FAVM}	Max. average on-state current	9244 A	$T_c = 85^\circ C$	Half sine pulse
I_{FRMS}	Max. RMS on-state current	14520 A	$T_c = 85^\circ C$	Half sine pulse
I_{FSM}	Max. peak non-repetitive surge current	64000 A	$t_p = 8.3 \text{ ms}$	$V_R = 0 \text{ V}$
		60000 A	$t_p = 10 \text{ ms}$	Half sine pulse
$\int I^2 dt$	Max. surge current integral	17049 kA ² s	$t_p = 8.3 \text{ ms}$	$V_R = 0 \text{ V}$
		18000 kA ² s	$t_p = 10 \text{ ms}$	Half sine pulse
$V_{F_{max}}$	Max. on-state voltage	0.920 V	$I_F = 5000 \text{ A}$	
		1.030 V	$I_F = 8000 \text{ A}$	
V_{FO}	Max. Threshold voltage	0.780 V		
r_F	Max. Slope resistance	0.031 mΩ	$I_F = 7000 \dots 21000 \text{ A}$	
Q_{rr}	Typ. Recovered charge	400 μC	$I_F = 1000 \text{ A}, di/dt = -30 \text{ A}/\mu\text{s},$ $V_R = 100 \text{ V}$	

Unless otherwise specified $T_j = 180^\circ C$

Thermal characteristics

T_j	Operating junction temperature range	-40...180 °C	
T_{stg}	Storage temperature range	-40...180 °C	
$R_{th(j-c)}$	Thermal resistance junction to case	7.4 K/kW	Anode side cooled
		23.5 K/kW	Cathode side cooled
		5.6 K/kW	Double side cooled
$R_{th(c-h)}$	Thermal resistance case to heatsink	6.7 K/kW	Anode side cooled
		8.0 K/kW	Cathode side cooled
		3.6 K/kW	Double side cooled




Fig. 2 Transient thermal impedance (junction-to-case) vs. time in analytical and graphical forms.

On-state characteristics




Fig. 3 Forward current vs. forward voltage (max. values).

Surge current characteristics




Fig. 4 Surge forward current vs. pulse length, half sine wave, single pulse,
 $V_R = 0\text{ V}$, $T_j = T_{jmax}$

Surge current characteristics




Fig. 5 Surge forward current vs. number of pulses, half sine wave, $T_j = T_{jmax}$

Forward power loss




Fig. 6 Forward power loss vs. average forward current, sine waveform, $f = 50\text{ Hz}$, $T = 1/f$

Forward power loss




Fig. 7 Forward power loss vs. average forward current, square waveform, $f = 50$ Hz, $T = 1/f$




Fig. 8 Forward power loss vs. average forward current, sine waveform, $f = 50$ Hz, $T = 1/f$




Fig. 9 Max. case temperature vs. aver. forward current, square waveform, $f = 50$ Hz, $T = 1/f$

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



**ABB Switzerland Ltd
Semiconductors
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland**

Doc. No. 5SYA1178-00 March 07

Telephone	+41 (0)58 586 1419
Fax	+41 (0)58 586 1306
Email	abbsem@ch.abb.com
Internet	www.abb.com/semiconductors