

V_{DRM} = 4200 V
 $I_{T(AV)M}$ = 1150 A
 $I_{T(RMS)}$ = 1800 A
 I_{TSM} = $17.3 \cdot 10^3$ A
 V_{TO} = 0.95 V
 r_T = 0.575 mΩ

Phase Control Thyristor


5STP 12F4200

Doc. No. 5SYA1021-07 Nov. 13

- Patented free-floating silicon technology
- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability

Blocking

Maximum rated values¹⁾

Parameter	Symbol	Conditions	5STP 12F4200	Unit
Max repetitive peak forward and reverse blocking voltage	V_{DRM} , V_{RRM}	$f = 50$ Hz, $t_p = 10$ ms, $T_{vj} = 5 \dots 125$ °C, Note 1 	4200	V
Critical rate of rise of commutating voltage	dv/dt_{crit}	Exp. to $0.67 \cdot V_{DRM}$, $T_{vj} = 125$ °C	1000	V/μs

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward leakage current	I_{DRM}	V_{DRM} , $T_{vj} = 125$ °C			200	mA
Reverse leakage current	I_{RRM}	V_{RRM} , $T_{vj} = 125$ °C			200	mA

Note 1: Voltage de-rating factor of 0.11% per °C is applicable for T_{vj} below +5 °C.

Mechanical data

Maximum rated values¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Mounting force	F_M		14	22	24	kN
Acceleration	a	Device unclamped			50	m/s ²
Acceleration	a	Device clamped			100	m/s ²

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Weight	m				0.6	kg
Housing thickness	H	$F_M = 22$ kN, $T_a = 25$ °C	26.1		26.5	mm
Surface creepage distance	D_s		25			mm
Air strike distance	D_a		14			mm

1) Maximum rated values indicate limits beyond which damage to the device may occur

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



On-state*Maximum rated values¹⁾*

Parameter	Symbol	Conditions	min	typ	max	Unit
Average on-state current	$I_{T(AV)M}$	Half sine wave, $T_c = 70^\circ C$			1150	A
RMS on-state current	$I_{T(RMS)}$				1800	A
Peak non-repetitive surge current	I_{TSM}	$t_p = 10 \text{ ms}, T_{vj} = 125^\circ C$, sine half wave, $V_D = V_R = 0 \text{ V}$, after surge			$17 \cdot 10^3$	A
Limiting load integral	I^2t				$1.5 \cdot 10^6$	A^2s
Peak non-repetitive surge current	I_{TSM}	$t_p = 10 \text{ ms}, T_{vj} = 125^\circ C$, sine half wave, $V_R = 0.6 \cdot V_{RRM}$, after surge			$12 \cdot 10^3$	A
Limiting load integral	I^2t				$720 \cdot 10^3$	A^2s

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
On-state voltage	V_T	$I_T = 2000 \text{ A}, T_{vj} = 125^\circ C$			2.1	V
Threshold voltage	$V_{(T0)}$				0.95	V
Slope resistance	r_T	$I_T = 600 \text{ A} - 1800 \text{ A}, T_{vj} = 125^\circ C$			0.575	$\text{m}\Omega$
Holding current	I_H	$T_{vj} = 25^\circ C$			80	mA
		$T_{vj} = 125^\circ C$			60	mA
Latching current	I_L	$T_{vj} = 25^\circ C$			500	mA
		$T_{vj} = 125^\circ C$			200	mA

Switching*Maximum rated values¹⁾*

Parameter	Symbol	Conditions	min	typ	max	Unit
Critical rate of rise of on-state current	di/dt_{crit}	$T_{vj} = 125^\circ C, I_{TRM} = 2000 \text{ A}, V_D \leq 0.67 \cdot V_{DRM}, I_{FG} = 2 \text{ A}, t_r = 0.5 \mu\text{s}$	Cont. $f = 50 \text{ Hz}$		100	$\text{A}/\mu\text{s}$
			Cont. $f = 1 \text{ Hz}$		1000	$\text{A}/\mu\text{s}$
Circuit-commutated turn-off time	t_q	$T_{vj} = 125^\circ C, I_{TRM} = 2000 \text{ A}, V_R = 200 \text{ V}, di_T/dt = -1.5 \text{ A}/\mu\text{s}, V_D \leq 0.67 \cdot V_{DRM}, dv_D/dt = 20 \text{ V}/\mu\text{s}$			900	μs

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Reverse recovery charge	Q_{rr}	$T_{vj} = 125^\circ C, I_{TRM} = 2000 \text{ A}, V_R = 200 \text{ V}, di_T/dt = -1.5 \text{ A}/\mu\text{s}$	1400		2400	μAs
Reverse recovery current	I_{RM}		40		54	A
Gate turn-on delay time	t_{gd}	$T_{vj} = 25^\circ C, V_D = 0.4 \cdot V_{RM}, I_{FG} = 2 \text{ A}, t_r = 0.5 \mu\text{s}$			2	μs

Triggering

Maximum rated values¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Peak forward gate voltage	V_{FGM}				12	V
Peak forward gate current	I_{FGM}				10	A
Peak reverse gate voltage	V_{RGM}				10	V
Average gate power loss	$P_{G(AV)}$		see Fig. 7			W

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Gate-trigger voltage	V_{GT}	$T_{vj} = 25^\circ C$			2.6	V
Gate-trigger current	I_{GT}	$T_{vj} = 25^\circ C$			400	mA
Gate non-trigger voltage	V_{GD}	$V_D = 0.4 \cdot V_{DRM}, T_{vjmax} = 125^\circ C$			0.3	V
Gate non-trigger current	I_{GD}	$V_D = 0.4 \cdot V_{DRM}, T_{vjmax} = 125^\circ C$			10	mA

Thermal

Maximum rated values¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Operating junction temperature range	T_{vj}				125	°C
Storage temperature range	T_{stg}		-40		140	°C

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Thermal resistance junction to case,	$R_{th(j-c)}$	Double-side cooled $F_m = 14 \dots 24 \text{ kN}$			17	K/kW
	$R_{th(j-c)A}$	Anode-side cooled $F_m = 14 \dots 24 \text{ kN}$			33	K/kW
	$R_{th(j-c)C}$	Cathode-side cooled $F_m = 14 \dots 24 \text{ kN}$			35	K/kW
Thermal resistance case to heatsink,	$R_{th(c-h)}$	Double-side cooled $F_m = 14 \dots 24 \text{ kN}$			4	K/kW
	$R_{th(c-h)}$	Single-side cooled $F_m = 14 \dots 24 \text{ kN}$			8	K/kW

Analytical function for transient thermal impedance:

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

i	1	2	3	4
$R_i(\text{K/kW})$	10.350	3.760	2.290	0.670
$\tau_i(\text{s})$	0.3723	0.0525	0.0057	0.0023




Fig. 1 Transient thermal impedance (junction-to-case) vs. time




Fig. 2 On-state voltage characteristics



Fig. 3 On-state voltage characteristics
 $T_{vj} = 125^\circ\text{C}$, 10 ms half sine

Fig. 4 On-state power dissipation vs. mean on-state current, turn-on losses excluded




Fig. 5 Max. permissible case temperature vs. mean on-state current, switching losses ignored




Fig. 6 Recommended gate current waveform




Fig. 7 Max. peak gate power loss




Fig. 8 Reverse recovery charge vs. decay rate of on-state current




Fig. 9 Peak reverse recovery current vs. decay rate of on-state current

Turn-on and Turn-off losses




Fig. 10 Turn-on energy, half sinusoidal waves




Fig. 11 Turn-on energy, rectangular waves




Fig. 12 Turn-off energy, half sinusoidal waves




Fig. 13 Turn-off energy, rectangular waves




Fig. 14 Current and voltage waveforms at turn-off

Total power loss for repetitive waveforms:

$$P_{TOT} = P_T + W_{on} \cdot f + W_{off} \cdot f$$

where

$$P_T = \frac{1}{T} \int_0^T I_T \cdot V_T(I_T) dt$$

Fig. 15 Relationships for power loss




Fig. 16 Device Outline Drawing

Related documents:

- | | |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------|
| 5SYA 2020 | Design of RC-Snubber for Phase Control Applications |
| 5SYA 2049 | Voltage definitions for phase control thyristors and diodes |
| 5SYA 2051 | Voltage ratings of high power semiconductors |
| 5SYA 2034 | Gate-Drive Recommendations for PCT's |
| 5SYA 2036 | Recommendations regarding mechanical clamping of Press Pack High Power Semiconductors |
| 5SZK 9104 | Specification of environmental class for pressure contact diodes, PCTs and GTO, STORAGE available on request, please contact factory |
| 5SZK 9105 | Specification of environmental class for pressure contact diodes, PCTs and GTO, TRANSPORTATION available on request, please contact factory |

Please refer to <http://www.abb.com/semiconductors> for current version of documents.

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



**ABB Switzerland Ltd
Semiconductors**
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Doc. No. 5SYA1021-07 Nov. 13

Telephone +41 (0)58 586 1419
Fax +41 (0)58 586 1306
Email abbsem@ch.abb.com
Internet www.abb.com/semiconductors