

# SKiiP 3614 GB12E4-6DUW



**SKiiP® 4**

2-pack-integrated intelligent Power System

## SKiiP 3614 GB12E4-6DUW

### Features

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- $T_{j\max} = 175^\circ\text{C}$
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

### Typical Applications\*

- Renewable energies
- Traction
- Elevators
- Industrial drives

### Remarks

For further information please refer to SKiiP®4 Technical Explanation


### Footnote

<sup>1)</sup> With assembly of suitable MKP capacitor per terminal

<sup>2)</sup> The specified maximum operation junction temperature  $T_{vjop}$  is  $150^\circ\text{C}$

Absolute Maximum Ratings		Values		Unit
Symbol	Conditions			
<b>System</b>				
$V_{CC}$ <sup>1)</sup>	Operating DC link voltage	900		V
$V_{isol}$	DC, $t = 1 \text{ s}$ , each polarity	4300		V
$I_t(\text{RMS})$	per AC terminal, rms, sinusoidal current	500		A
$I_{\max}(\text{peak})$	max. peak current of power section	5400		A
$I_{FSM}$	$T_j = 175^\circ\text{C}$ , $t_p = 10 \text{ ms}$ , sin 180°	16547		A
$I^2t$	$T_j = 175^\circ\text{C}$ , $t_p = 10 \text{ ms}$ , diode	1369		kA <sup>2</sup> s
$f_{\text{out}}$	fundamental output frequency (sinusoidal)	1		kHz
$T_{\text{stg}}$	storage temperature	-40 ... 85		°C
<b>IGBT</b>				
$V_{CES}$	$T_j = 25^\circ\text{C}$	1200		V
$I_c$	$T_j = 175^\circ\text{C}$	4664		A
	$T_s = 25^\circ\text{C}$	3792		A
$I_{Cnom}$		3600		A
$T_j$ <sup>2)</sup>	junction temperature	-40 ... 175		°C
<b>Diode</b>				
$V_{RRM}$	$T_j = 25^\circ\text{C}$	1200		V
$I_F$	$T_j = 175^\circ\text{C}$	3558		A
	$T_s = 25^\circ\text{C}$	2821		A
$I_{Fnom}$		3600		A
$T_j$ <sup>2)</sup>	junction temperature	-40 ... 175		°C
<b>Driver</b>				
$V_s$	power supply	19.2 ... 28.8		V
$V_{IH}$	input signal voltage (high)	$V_s + 0.3$		V
$dv/dt$	secondary to primary side	75		kV/μs
$f_{sw}$	switching frequency	5		kHz

Symbol	Conditions	min.	typ.	max.	Unit
<b>IGBT</b>					
$V_{CE(\text{sat})}$	$I_c = 3600 \text{ A}$ at terminal	2.01	2.26		V
	$T_j = 150^\circ\text{C}$	2.49	2.69		V
$V_{CE0}$		0.80	0.90		V
	$T_j = 150^\circ\text{C}$	0.70	0.80		V
$r_{CE}$	$I_c = 3600 \text{ A}$ at terminal	0.34	0.38		mΩ
	$T_j = 150^\circ\text{C}$	0.50	0.53		mΩ
$E_{\text{on}} + E_{\text{off}}$	$I_c = 3600 \text{ A}$ $T_j = 150^\circ\text{C}$	1405			mJ
	$V_{CC} = 600 \text{ V}$	2520			mJ
$R_{\text{th(j-s)}}$	per IGBT switch			0.0106	K/W
$R_{\text{th(j-r)}}$	per IGBT switch			0.0077	K/W



S64

# SKiiP 3614 GB12E4-6DUW



**SKiiP® 4**

2-pack-integrated intelligent Power System

## SKiiP 3614 GB12E4-6DUW

### Features

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- $T_{j\max} = 175^\circ\text{C}$
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

### Typical Applications\*

- Renewable energies
- Traction
- Elevators
- Industrial drives

### Remarks


For further information please refer to SKiiP®4 Technical Explanation

### Footnote

1) With assembly of suitable MKP capacitor per terminal

2) The specified maximum operation junction temperature  $T_{vjop}$  is  $150^\circ\text{C}$

Characteristics		Conditions	min.	typ.	max.	Unit
Symbol						
<b>Diode</b>						
$V_F = V_{EC}$	$I_F = 3600 \text{ A}$ at terminal	$T_j = 25^\circ\text{C}$		2.33	2.65	V
		$T_j = 150^\circ\text{C}$		2.35	2.66	V
$V_{FO}$		$T_j = 25^\circ\text{C}$		1.30	1.50	V
		$T_j = 150^\circ\text{C}$		0.90	1.10	V
$r_F$	at terminal	$T_j = 25^\circ\text{C}$		0.29	0.32	$\text{m}\Omega$
		$T_j = 150^\circ\text{C}$		0.40	0.43	$\text{m}\Omega$
$E_{rr}$	$I_F = 3600 \text{ A}$ $T_j = 150^\circ\text{C}$	$V_R = 600 \text{ V}$		238		$\text{mJ}$
		$V_R = 900 \text{ V}$		300		$\text{mJ}$
$R_{th(j-s)}$	per diode switch				0.0187	K/W
$R_{th(j-r)}$	per diode switch				0.0158	K/W
<b>Driver</b>						
$V_s$	supply voltage non stabilized		19.2	24	28.8	V
$I_{SO}$	bias current @ $V_s = 24\text{V}$ , $f_{sw} = 0$ , $I_{AC} = 0$			430		$\text{mA}$
$I_s$	$k_1 = 48 \text{ mA/kHz}$ , $k_2 = 0.286 \text{ mA/A}$ , $f_{out} = 50\text{Hz}$ , sinusoidal current		= 430	+ $k_1 * f_{sw}$	+ $k_2 * I_{AC}$	$\text{mA}$
$V_{IT+}$	input threshold voltage (HIGH)		0,7* $V_s$			V
$V_{IT-}$	input threshold voltage (LOW)			0,3* $V_s$		V
$R_{IN}$	input resistance			13		$\text{k}\Omega$
$C_{IN}$	input capacitance			1		$\text{nF}$
$t_{pRESET}$	error memory reset time		1300		2900	ms
$t_{pReset(OCP)}$	Over current reset time					$\mu\text{s}$
$t_{TD}$	top / bottom switch interlock time			3		$\mu\text{s}$
$t_{jitter}$	jitter clock time			52	58	ns
$t_{SIS}$	short pulse suppression time			0.6		$\mu\text{s}$
$t_{POR}$	Power-On-Reset completed			3.5		s
$I_{digout}$	digital output sink current (HALT-signal)				16	$\text{mA}$
$V_{it+ HALT}$	input threshold voltage HIGH HALT (Low -->High)		0,6* $V_s$			V
$V_{it-HALT}$	input threshold voltage LOW HALT (High --> Low)			0,4* $V_s$		V
$t_d(\text{err})$	Error delay time (from detection to HALT), (depends on kind of error)		1.8		170	$\mu\text{s}$
$I_{TRIPSC}$	over current trip level		5290	5400	5510	$A_{PEAK}$
$I_{LL}$				n.a.		$A_{PEAK}$
$T_{trip}$	over temperature trip level		128	135	142	$^\circ\text{C}$
$T_{DriverTrip}$	over temperature PCB trip level		113	120	124	$^\circ\text{C}$
$V_{DCtrip}$	over voltage trip level, can be deactivated via CAN interface,		950	980	1010	V
$V_{DCtripLL}$				n.a.		V



S64

# SKiiP 3614 GB12E4-6DUW



**SKiiP® 4**

2-pack-integrated intelligent Power System

## SKiiP 3614 GB12E4-6DUW

### Features

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- $T_{j\max} = 175^\circ\text{C}$
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

### Typical Applications\*

- Renewable energies
- Traction
- Elevators
- Industrial drives

### Remarks


For further information please refer to  
SKiiP®4 Technical Explanation

### Footnote

<sup>1)</sup> With assembly of suitable MKP capacitor per terminal

<sup>2)</sup> The specified maximum operation junction temperature  $T_{vjop}$  is  $150^\circ\text{C}$

Characteristics		Conditions	min.	typ.	max.	Unit
Symbol	System					
$t_{d(on)IO}$	$V_{CC} = 600 \text{ V}$ $I_C = 3600 \text{ A}$ $T_j = 25^\circ\text{C}$	turn on propagation delay time		2.8		$\mu\text{s}$
$t_{d(off)IO}$		turn off propagation delay time		3.8		$\mu\text{s}$
$dV_{CE}/dt_{on}$	$T_j = 25^\circ\text{C}$ $V_{CC} = 600 \text{ V}$	$I_C = 0 \text{ A}$		9		$\text{kV}/\mu\text{s}$
$dV_{CE}/dt_{off}$		$I_C = 3600 \text{ A}$		3		$\text{kV}/\mu\text{s}$
$dV_{CE}/dt_{off}$		$I_C = 3600 \text{ A}$		3		$\text{kV}/\mu\text{s}$
$R_{th(s-a)}$	flow rate = 15 l/min, $T_{Fluid}=40^\circ\text{C}$ , water/glycol ratio 50%:50%				0.0051	K/W
$R_{CC+EE'}$	terminals to chip, $T_s = 25^\circ\text{C}$		0.045			$\text{m}\Omega$
$L_{CE}$	commutation inductance		3			nH
$C_{CHC}$	coupling capacitance secondary to heat sink			8.4		nF
$C_{ps}$	coupling capacitance primary to secondary			0.102		nF
$I_{CES} + I_{RD}$	$V_{GE} = 0 \text{ V}$ , $V_{CE} = 1200 \text{ V}$ , $T_j = 25^\circ\text{C}$		0.527			mA
$M_{dc}$	DC terminals	6		8		Nm
$M_{ac}$	AC terminals	13		15		Nm
$w$	SKiiP System w/o heat sink			4.84		kg
$w_h$	heat sink			5.77		kg



S64

Isolation coordination acc. to EN 50178 and IEC 61800-5-1	
Maximum grid RMS voltage, line-to-line, grounded delta mains	480V+20%
Installation altitude for maximum grid RMS voltage, line-to-line, grounded delta mains	4000m
Maximum grid RMS voltage, line-to-line, star point grounded mains	480V+20%
Installation altitude for maximum grid RMS voltage, line-to-line, star point grounded mains	8000m
Maximum transient peak voltage between low voltage circuit and mains	1900V
Pollution degree acc. to IEC 60664-1 outside the moulded power section	2
Oversupply cat. acc. to IEC 60664-1 for mains	III
Oversupply cat. acc. to UL 840 within mains	I
Oversupply cat. acc. to UL 840 between mains and ground	III
Oversupply cat. acc. to UL 840 between mains and low voltage circuit	III
Basic isolation	between heat sink and mains
Reinforced isolation	between low voltage circuit and mains
Protection level acc. to IEC 60529	IP00

## Environmental conditions acc. to IEC 60721

	Storage	Transportation	Operation stationary use at weather protected locations	Operating ground vehicle installations	Operating ship environment
Climatic conditions	1K2 <sub>(1)</sub>	2K2 <sub>(1)</sub>	3K3 <sub>(1)</sub>	5K1 <sub>(1)</sub>	6K1 <sub>(1)</sub>
Biological conditions	1B1	2B1	3B1	5B1	6B1
Chemically active substances (excluded: salt spray)	1C2	2C1	3C2	5C2	6C2
Mechanically active substances	1S1	2S1	3S1	5S1	6S1
Mechanical conditions	1M3	(4)	3M6 <sub>(2)</sub>	5M3 <sub>(3)</sub>	6M3
Contaminating fluids	--	--	--	5F1	--

(1) expanded temperature range: -40°C / +85°C. Please note: by operation near 85°C the life time of product is reduced.

(2) 3M7 possible, but due to the mechanic load capacity of external components like DC-Link capacitors limited to 3M6

(3) 5M3 without impact of foreign bodies, stones

(4) no declaration due to customer-specific packing

# SKiiP 3614 GB12E4-6DUW




Fig. 1: Typical IGBT output characteristics




Fig. 2: Typical diode output characteristics




Fig. 3: Typical switching energy  $E = f(I_c)$




Fig. 4: Typical switching energy  $E = f(I_c)$




Fig. 5: Transient thermal impedance  $Z_{th(j-s)}$




Fig. 6: Transient thermal impedance  $Z_{th(j-r)}$

# SKiiP 3614 GB12E4-6DUW




Fig. 7: Transient thermal impedance  $Z_{th(s-a)}$

R <sub>th</sub> [K/W]					
	1	2	3	4	5
$Z_{th(j-s)}$ I	0,0007	0,0038	0,0042	0,0013	0,0006
$Z_{th(j-s)}$ D	0,0013	0,0067	0,0074	0,0022	0,0011
$Z_{th(j-r)}$ I	0,0009	0,0021	0,0026	0,0016	0,0005
$Z_{th(j-r)}$ D	0,0011	0,0033	0,0061	0,0030	0,0023
$Z_{th(s-a)}$	0,0017	0,0034			

tau [s]					
	1	2	3	4	5
$Z_{th(j-s)}$ I	3,6500	0,4100	0,0650	0,0090	0,0008
$Z_{th(j-s)}$ D	3,6500	0,4100	0,0650	0,0090	0,0008
$Z_{th(j-r)}$ I	2,7731	0,5071	0,0555	0,0105	0,0010
$Z_{th(j-r)}$ D	2,6032	0,3312	0,0480	0,0109	0,0006
$Z_{th(s-a)}$	32,3020	5,9361			

Fig. 8: Coefficients of thermal impedances




Fig. 9: Thermal resistance  $R_{th(s-a)}$  versus flow rate  $V$





Fig. 10: Pressure drop  $\Delta p$  versus flow rate  $V$

# SKiiP 3614 GB12E4-6DUW



## System

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

\* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.